

HEATERS

Rekord proves a range of premium, oil-powered heaters that adhere to the highest international quality standards. These durable, reliable and easy installable portable units are ideal for heating large spaces such as structures, tents, warehouses or farming facilities.

With a variety of models available, you can choose the right heater to meet your specific needs without the risk of oversizing.

The heaters offer a minimum heating power of 55 kW.

- **Reliable Performance:** Our selection of products from top manufacturers deliver maximum efficiency.
- **Versatile Solutions:** With so many models to choose from, you'll find the right heater to meet your needs.
- **Exceptional Portability:** Easy-to-install units that are portable and ideal for heating large spaces.



HEATERS



Specifications:

Manufacturer:	Biemmedue	Thermobile	Master	Arcotherm / Master	Arcotherm / Master
Model:	Jumbo 235	IMA 200	BV 691 S	EC85 / BV290E	EC55 / BV170E
Fuel consumption:	4.9 gph (18,65 l/h)	5 gph (19,41 l/h)	5.6 gph (21,44 l/h)	1.89 / 2 gph (7,17 / 8,1 l/h)	1.2 / 1 gph (4,6 / 3,9 l/h)
Power consumption:	1,86 [kW]	15 A	12,6 A	1140 W / 4,6 A	850 W / 0,8 A
Power:	235,0 kW	200,0 kW	do 225 kW	85 Kw	55,0 kW / 49,0 kW
Dimensions: (l/w/h)	39 x 88 x 62 in. (1000 x 2240 x 1580 mm)	138 x 45 x 59 in. (3510 x 1150 x 1500 mm)	90 x 45 x 59 in. (2300 x 1000 x 2000 mm)	68.8 x 21 x 46 in. (1750 x 540 x 1170 mm)	68.8 x 21 x 46 in. (1750 x 540 x 1170 mm)
Net weight:	773.8 lbs. (351 kg)	992 lbs. (450 kg) +heater frame	837.7 lbs. (380 kg)	242.5 lbs. (110 kg)	176 lbs. /154 lbs. (80 kg/70 kg)
Air supply:	2 x VENT COMBO Ø500 sleeve	2 x VENT COMBO Ø500 sleeve	2 x VENT COMBO Ø500 sleeve	2 x VENT COMBO Ø500 sleeve	1 x VENT COMBO sleeve
Non-insulated structure:	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)
Insulated Structure:	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)	1 kW ~ 16 sq ft. (1,5 m²)



CHECK
ONLINE

